## NSN 5930-01-212-1551

**Hazardous Locations/environmental Protection:** 

Push Switch - Page 1 of 2

**Body Style:** Panel mount

Overall Length: 0.750 inches



View Online at https://aerobasegroup.com/nsn/5930-01-212-1551

Corrosion resistant and fungus resistant and moisture resistant

Overall Height:			
2.320 inches			
Overall Width:			
0.750 inches			
Body Length:			
0.688 inches			
Body Width:			
0.688 inches			
Body Height:			
2.240 inches			
Case Material:			
Metal			
Actuator Length:			
0.620 inches			
Actuator Style:			
Rectangular			
Actuator Height:			
0.080 inches			
Actuator Width:			
0.620 inches			
Actuator Color:			
White single actuator			
Illuminated Actuator Color:			
White single actuator			
Actuator Inscription:			
Maint; /aux single actuator			
Maximum Voltage Rating In Volts:			
28.0 dc			
Inclosure Type:			
Fully enclosed			
Mounting Method:			
Panel			
Nonpile-up Contact Arrangement:			
2 pole, double throw, one position momentary single switch unit			
Contact Load Current Rating At Maximum Rated Voltage:			
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc			

## NSN 5930-01-212-1551

Push Switch - Page 2 of 2



Precious	Material	<b>And</b>	Location:

Contacts silver and contact surfaces gold

**Unable To Decode:** 

Unable to decode and unable to decode

**Terminal Type And Quantity:** 

5 tab, solder lug and 6 turret

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0