# NSN 5930-01-212-1551

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-212-1551

# **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Corrosion resistant and fungus resistant and moisture resistant

# **Overall Length:**

0.750 inches

#### **Overall Height:**

2.320 inches

## **Overall Width:**

0.750 inches

- **Body Length:**
- 0.688 inches

Body Width:

# 0.688 inches

Body Height:

# 2.240 inches

Case Material:

Metal

Actuator Length:

0.620 inches

#### **Actuator Style:**

Rectangular

#### Actuator Height:

0.080 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

White single actuator

#### Illuminated Actuator Color:

White single actuator

#### **Actuator Inscription:**

Maint; /aux single actuator

# Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc

# NSN 5930-01-212-1551

Push Switch - Page 2 of 2



Precious Material And Location: Contacts silver and contact surfaces gold Unable To Decode: Unable to decode and unable to decode Terminal Type And Quantity: 5 tab, solder lug and 6 turret Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A053a0