NSN 5930-01-212-4758

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-212-4758

| view Online at https://aerobasegroup.com/hsh/5550-01-212-4750 |
|--|
| Body Style: |
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Explosion proof and moisture resistant |
| Overall Length: |
| 0.740 inches |
| Overall Height: |
| 3.060 inches |
| Overall Width: |
| 0.740 inches |
| Body Length: |
| 0.740 inches |
| Body Width: |
| 0.740 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Width: |
| 0.740 inches |
| Actuator Color: |
| White single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| End Application: |
| 5840-01-085-1606 operations control |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes |
| inductive ac and 1.500 amperes lamp ac |
| Precious Material And Location: |
| Contact surfaces gold and contacts silver |
| Unable To Decode: |
| Unable to decode and unable to decode |

12 pin

Terminal Type And Quantity:

NSN 5930-01-212-4758

Push Switch - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0