NSN 5930-01-212-4760

Push Switch - Page 1 of 2

Unable To Decode:

Unable to decode and unable to decode



View Online at https://aerobasegroup.com/nsn/5930-01-212-4760

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and moisture resistant
Overall Length:
0.740 inches
Overall Height:
3.060 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.740 inches
Case Material:
Metal
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Width:
0.740 inches
Actuator Color:
Red single actuator and red single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
5840-01-088-6642 weapons locating sy
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 2.500 amperes inductive dc and 1.500 amperes lamp dc and 5.000 amperes resistive ac and 2.500 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Horizontal split lens
Precious Material And Location:
Contact surfaces gold and contacts silver

NSN 5930-01-212-4760

Push Switch - Page 2 of 2



Terminal Type And Quantity:
12 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig:

A053a0