# NSN 5930-01-212-5737

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-212-5737

# Body Style:

Hole mounted

### **Overall Length:**

0.780 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

0.500 inches

#### **Overall Height:**

0.533 inches

#### **Overall Width:**

0.400 inches

#### **Body Length:**

0.780 inches

#### Body Width:

0.250 inches

#### Body Height:

0.440 inches

# Case Material:

Plastic

### **Unthreaded Mounting Hole Diameter:**

0.088 inches

## Actuator Length:

0.120 inches

# Actuator Style:

Rectangular

#### Actuator Height:

0.093 inches

# Actuator Width:

0.120 inches

## **Actuator Free Position Height:**

0.093 inches

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Radio set, an/prc-68a

#### Inclosure Type:

Fully enclosed

# Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

# Switch Actuating Force:

8.0 ounces

#### **Actuator Movement:**

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

# NSN 5930-01-212-5737

Sensitive Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000

amperes inductive ac and 1.500 amperes lamp ac

# Terminal Type And Quantity:

4 printed circuit

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A053a0