NSN 5930-01-212-5737

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-212-5737

Body Style:
Hole mounted
Overall Length:
0.780 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
0.533 inches
Overall Width:
0.400 inches
Body Length:
0.780 inches
Body Width:
0.250 inches
Body Height:
0.440 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.088 inches
Actuator Length:
0.120 inches
Actuator Style:
Rectangular
Actuator Height:
0.093 inches
Actuator Width:
0.120 inches
Actuator Free Position Height:
0.093 inches
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Radio set, an/prc-68a
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
8.0 ounces
Actuator Movement:

Actuator Movement

Between 0.050 pretravel inches and 0.012 overtravel inches and 0.020 differential inches

NSN 5930-01-212-5737

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Terminal	Type	And	Quantity:

4 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0