NSN 5930-01-212-7275

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-212-7275

Hazardous Locations/environmental Protection:
Shock proof
Overall Length:
3.520 inches
Overall Height:
2.120 inches
Overall Width:
1.740 inches
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.620 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.250 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
2 single section rear
Throw Quantity:
2 single section rear
Mounting Method:
Bracket single mounting facility and threaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
440.0 highest ac voltage rating at sea level
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Switch Actuator Stop Device Type:
Fixed stop single actuator
Contact Load Current Rating:
7.5 amperes resistive load highest ac voltage rating at sea level
Shelf Life:
N/a

N/a

NSN 5930-01-212-7275Rotary Switch - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A052b0