

View Online at <https://aerobasegroup.com/nsn/5930-01-212-7830>

Inside Diameter:

0.125 inches all connections

Overall Length:

8.938 inches

Overall Height:

4.250 inches

Overall Width:

7.750 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Mounting Facility Centers:

8.250 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 130.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

27 all pressure connection

Contact Action Stimulus:

Decrease

Thread Size:

0.125 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point not adjustable

Contact Adjustment Type:

Internal actuation point hex nut

Contact Voltage Rating In Volts:

480.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Frequency In Hertz:

60.0 second voltage

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/lugs

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0