## NSN 5930-01-213-0317

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-213-0317

## **Body Style:**

Hole mounted

## Hazardous Locations/environmental Protection:

Acid resistant and watertight and shock resistant

## **Overall Length:**

7.500 inches

## **Case Material:**

Metal

## Actuator Style:

Round

## Actuator Diameter:

0.500 inches

#### Actuator Height:

1.500 inches

#### **Housing Height:**

## 2.969 inches

Housing Length:

4.500 inches

## Housing Width:

6.000 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

3.875 inches

## Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

5.375 inches

## Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

#### **End Application:**

6110-01-155-7000

## Inclosure Type:

Fully enclosed

#### Nonpile-up Contact Arrangement:

3 pole, double throw, both positions maintained single switch unit

#### Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 10.000 amperes resistive ac

## **Special Features:**

Cam actuated with worm gear

## **Terminal Type And Quantity:**

9 screw

Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5930-01-213-0317

Sensitive Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A053a0

