NSN 5930-01-213-1359

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-213-1359

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
0.740 inches
Overall Height:
2.960 inches
Overall Width:
0.740 inches
Body Width:
0.740 inches
Body Height:
0.740 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.300 inches
Actuator Width:
0.740 inches
Actuator Color:
Yellow single actuator and white single actuator
Illuminated Actuator Color:
Yellow single actuator and white single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow, lower half of actuator white
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Gun fire control system, mk 68
Mounting Surface To Terminal End Distance:
2.660 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Rfi shielding
Nonpile-up Contact Arrangement:
4 note double throw one position momentary single switch unit

NSN 5930-01-213-1359

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

17 pin

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0