## NSN 5930-01-213-1903

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-01-213-1903

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Acid resistant and watertight and shock resistant
Overall Length:
7.500 inches
Overall Height:
4.500 inches
Overall Width:
2.969 inches
Case Material:
Metal
Actuator Style:
Round
Actuator Diameter:
0.500 inches
Actuator Height:
1.500 inches
Actuator Free Position Height:
1.500 inches
Housing Height:
2.969 inches
Housing Length:
4.500 inches
Housing Width:
6.000 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
3.875 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
5.375 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
250.000 milliamperes resistive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:

## NSN 5930-01-213-1903

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A053a0