NSN 5930-01-213-3495

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-213-3495

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Overall Length:

1.125 inches

Shaft Diameter:

0.125 inches single actuator

Shaft Length:

0.250 inches single actuator

Overall Diameter:

0.500 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

2 single section rear

Throw Quantity:

2 single section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.250 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, slotted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

60.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contact surfaces silver and rotor blade surfaces gold

Precious Material:

Silver and gold

NSN 5930-01-213-3495

Rotary Switch - Page 2 of 2



| Style | Des | siar | ato | r- |
|-------|-----|------|------|----|
| Otylo | | , gi | iato | |

Snap or line

Thread Series Designator:

Unf single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0