## NSN 5930-01-213-6137

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-213-6137

**Thread Class:** 

2b single mounting facility

**Overall Length:** 

8.807 inches

**Distance Between Mounting Facility Centers:** 

2.281 inches single mounting facility

**Individual Section Quantity:** 

7

**Pole Quantity:** 

1 single section front

**Mounting Facility Circle Radius:** 

3.219 inches single mounting facility

**Mounting Method:** 

Threaded hole single mounting facility

Thready Qty Per Inch (tpi):

20 single mounting facility

**Thread Size:** 

0.250 inches single mounting facility

**Contact Voltage Rating In Volts:** 

600.0 ac at sea level

**Switch Actuator Momentary Position:** 

Clockwise single actuator and counterclockwise single actuator

**Mounting Facility Pattern:** 

Four position circular single mounting facility

**Switch Actuator Indexing Position Quantity:** 

3 single actuator

**Criticality Code Justification:** 

7771

**Terminal Type:** 

Tab w/screw

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

30.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circuit selector

**Thread Series Designator:** 

Unc single mounting facility

**Reference Number Differentiating Characteristics:** 

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

## NSN 5930-01-213-6137

Rotary Switch - Page 2 of 2



Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0