

View Online at <https://aerobasegroup.com/nsn/5930-01-213-6293>

Inside Diameter:

0.125 inches single connection

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.250 inches

Overall Height:

2.500 inches

Overall Width:

3.188 inches

Body Length:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.164 inches

Longest Horizontal Distance Between Mounting Centers:

2.625 inches

Longest Vertical Distance Between Mounting Centers:

2.438 inches

Pressure Switch Type:

Gage

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port and automatic reset

Thready Qty Per Inch (tpi):

32 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

30.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position diagonal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

10.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+2.20 to 30.00 actuation point inches of mercury and +0.50 to 29.00 deactuation point inches of mercury

Contact Adjustment Type:

Internal actuation point hex nut with scale and internal deactuation point hex nut with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level third voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

60.0 third voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0