NSN 5930-01-214-0762

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-214-0762

| Hazardous Locations/environmental Protection: |
|---|
| Shock proof and vibration proof |
| Overall Length: |
| 0.500 inches |
| Overall Height: |
| 3.005 inches |
| Overall Width: |
| 1.880 inches |
| Individual Section Quantity: |
| 1 |
| Operating Tempurature Range: |
| -65.0 to 85.0 degrees celsius |
| Mounting Method: |
| Bracket single mounting facility |
| Actuator Type: |
| Thumbwheel single actuator |
| Contact Voltage Rating In Volts: |
| 28.0 dc at sea level |
| Switch Actuator Indexing Position Quantity: |
| 16 single actuator |
| Terminal Type: |
| Printed circuit |
| Contact Load Current Rating: |
| 125.0 milliamperes resistive load dc at sea level |
| Readout Indicator Marking: |
| 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, a, b, c, d, e, f single section |
| Contact Arrangement Truth Table: |
| Bcd, 1 pole - 16 positions single section |
| Color: |
| White single indicator marking |
| Precious Material And Location: |
| Contacts gold |
| Precious Material: |
| Gold |
| Style Designator: |
| Rectangular indicating |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5930-01-214-0762

Code Indicating Wheel Switch - Page 2 of 2



Fiig:

A052b0