NSN 5930-01-214-0772

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-214-0772

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof and vibration resistant and shock resistant
Body Length:
0.750 inches
Body Width:
0.750 inches
Body Height:
2.620 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.090 inches
Actuator Width:
0.620 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Reset/restart single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes
inductive ac and 2.000 amperes lamp ac
Special Features:
Switch guard included p/n 51056
Precious Material And Location:
Contacts silver

5 tab, solder lug and 6 turret

Terminal Type And Quantity:

NSN 5930-01-214-0772

Push Switch - Page 2 of 2



-			
٠.	hΔ	Iŧ.	ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0