

View Online at <https://aerobasegroup.com/nsn/5930-01-214-5272>

**Thread Class:**

2b second threaded hole

**Thread Length:**

0.562 inches first threaded hole

**Overall Length:**

2.750 inches

**End Application:**

Amplifier, radio frequency am-7061/wsc-6 (v)

**Operating Temperature Rating:**

Between 0.0 degrees celsius and 60.0 degrees celsius

**Mounting Method:**

Threaded hole

**Thready Qty Per Inch (tpi):**

32 second threaded hole

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.875 inches second threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

0.5 amperes inductive load second voltage

**Contact Adjustability:**

Actuation point not adjustable and deactuation point not adjustable

**Contact Stimulus Rating:**

1.10 actuation point gallons per minute and 1.00 deactuation point gallons per minute

**Contact Voltage Rating In Volts:**

50.0 dc at sea level second voltage

**Media For Which Designed:**

Liquid

**Thread Series Designator:**

Unf first threaded hole

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0