NSN 5930-01-214-5272

Flow Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-214-5272 **Thread Class:** 2b second threaded hole **Thread Length:** 0.562 inches first threaded hole **Overall Length:** 2.750 inches **End Application:** Amplifier, radio frequency am-7061/wsc-6 (v) **Operating Tempurature Rating:** Between 0.0 degrees celsius and 60.0 degrees celsius **Mounting Method:** Threaded hole Thready Qty Per Inch (tpi): 32 second threaded hole **Contact Action Stimulus:** Increase **Thread Size:** 0.875 inches second threaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary **Terminal Type:** Connector, receptacle **Contact Load Current Rating:** 0.5 amperes inductive load second voltage **Contact Adjustability:** Actuation point not adjustable and deactuation point not adjustable **Contact Stimulus Rating:** 1.10 actuation point gallons per minute and 1.00 deactuation point gallons per minute **Contact Voltage Rating In Volts:** 50.0 dc at sea level second voltage Media For Which Designed: Liquid **Thread Series Designator:** Unf first threaded hole Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A048b0