

View Online at <https://aerobasegroup.com/nsn/5930-01-214-6146>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

0.572 inches

Overall Height:

2.277 inches

Overall Width:

0.432 inches

Bushing Length:

0.438 inches

Body Length:

0.572 inches

Body Width:

0.364 inches

Actuator Style:

Round

Actuator Diameter:

0.432 inches

Actuator Height:

1.102 inches

Actuator Position-action Relationship:

Up position momentary and down position momentary and center position maintained

Actuator Position-locking Relationship:

Up position no locking action and down position no locking action and center position locked in

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Weapon system-aircraft, (ac-130h, mc-130h, ec-130e, hc-130)

Mounting Surface To Terminal End Distance:

0.706 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Criticality Code Justification:

Feat

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces gold

Test Data Document:

81349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab, solder lug

Specification Data:

96906-ms21436 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0