

View Online at <https://aerobasegroup.com/nsn/5930-01-215-0798>

**Body Style:**

Bushing mount

**Overall Length:**

0.625 inches

**Overall Height:**

1.600 inches

**Overall Width:**

0.270 inches

**Bushing Length:**

0.350 inches

**Body Length:**

0.500 inches

**Body Width:**

0.270 inches

**Body Height:**

0.350 inches

**Case Material:**

Plastic

**Actuator Style:**

Rectangular

**Actuator Height:**

0.450 inches

**Actuator Width:**

0.100 inches

**Actuator Position-action Relationship:**

Up position maintained and down position momentary

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**End Application:**

6625-01-094-7716 generator function

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 2.000 amperes resistive ac

**Special Features:**

Unthreaded bushing terminals at right angle

**Precious Material And Location:**

Contact and terminal surfaces gold and contacts silver

**Terminal Type And Quantity:**

3 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0