

View Online at <https://aerobasegroup.com/nsn/5930-01-215-2005>

**Hazardous Locations/environmental Protection:**

Shock proof and vibration proof

**Overall Length:**

3.760 inches

**Overall Height:**

1.780 inches

**Overall Width:**

1.150 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

6

**Longest Horizontal Distance Between Mounting Centers:**

3.590 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Operating Temperature Range:**

-65.0 to 85.0 degrees celsius

**Mounting Method:**

Bracket and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Features Provided:**

Rfi shielding

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

2 all actuators

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

125.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1 each section

**Contact Arrangement Truth Table:**

Decimal, 1 pole - 10 positions each section

**Special Features:**

Indicating wheels have stops after position one

**Color:**

White each indicator marking

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0