

View Online at <https://aerobasegroup.com/nsn/5930-01-215-6041>

**Thread Pitch Diameters:**

+9.450/+9.531 millimeters single mounting facility

**Thread Length:**

0.275 inches single mounting facility and 0.315 inches single mounting facility

**Width Between Flats:**

0.184 inches single actuator and 0.187 inches single actuator

**Overall Length:**

Between 1.870 inches and 1.990 inches

**First Flat Length:**

0.184 inches single actuator and 0.192 inches single actuator

**Shaft Diameter:**

0.236 inches single actuator and 0.239 inches single actuator

**Shaft Length:**

0.315 inches single actuator and 0.320 inches single actuator

**Overall Diameter:**

1.306 inches

**Individual Section Quantity:**

2

**Nonturn Device Type:**

Flatted bushing at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 each section front

**Throw Quantity:**

10 each section front

**Mounting Method:**

Threaded bushing w/panel seal single mounting facility

**Thread Size:**

10.0 millimeters single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round, parallel flatted, threaded hole single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

0.250 amperes resistive load dc at sea level

**Style Designator:**

Tap, circular, bushing mount

**Thread Series Designator:**

Iso m single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0