

View Online at <https://aerobasegroup.com/nsn/5930-01-215-6769>

**Thread Class:**

2a single mounting facility

**Thread Length:**

9.50 millimeters single mounting facility

**Overall Length:**

38.4 millimeters

**Shaft Diameter:**

6.4 millimeters single actuator

**Shaft Length:**

7.5 millimeters single actuator

**Overall Diameter:**

19.0 millimeters

**Individual Section Quantity:**

1

**Nonturn Device Type:**

Flatted bushing at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

9.5 millimeters single mounting facility

**Contact Voltage Rating In Volts:**

300.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

12 single actuator

**Shaft Type:**

Round, slotted single actuator

**Terminal Type:**

Tab, solder lug

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Pole contacts and moving and fixed contact surfaces silver

**Precious Material:**

Silver

**Style Designator:**

Miniature, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0