## NSN 5930-01-215-6769

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-215-6769

## Thread Class:

2a single mounting facility

### Thread Length:

9.50 millimeters single mounting facility

## **Overall Length:**

38.4 millimeters

#### Shaft Diameter:

6.4 millimeters single actuator

#### Shaft Length:

7.5 millimeters single actuator

#### **Overall Diameter:**

19.0 millimeters

#### Individual Section Quantity:

1

## Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

#### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

## **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

9.5 millimeters single mounting facility

#### **Contact Voltage Rating In Volts:**

300.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

12 single actuator

#### Shaft Type:

Round, slotted single actuator

#### **Terminal Type:**

Tab, solder lug

#### Switch Actuator Positioning Increment:

30.0 degrees single actuator

#### Switch Actuator Stop Device Type:

Fixed stop single actuator

#### **Contact Load Current Rating:**

2.0 amperes resistive load dc at sea level

## **Precious Material And Location:**

Pole contacts and moving and fixed contact surfaces silver

#### **Precious Material:**

Silver

#### Style Designator:

Miniature, bushing mount

# NSN 5930-01-215-6769

Rotary Switch - Page 2 of 2



**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A052b0