NSN 5930-01-215-7088

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-215-7088

| Body Style: | |
|---|--|
| Panel mounted | |
| Overall Length: | |
| 2.751 inches | |
| Overall Height: | |
| 0.750 inches | |
| Overall Width: | |
| 0.750 inches | |
| Body Width: | |
| 0.750 inches | |
| Body Height: | |
| 0.750 inches | |
| Case Material: | |
| Metal | |
| Actuator Length: | |
| 0.620 inches | |
| Actuator Style: | |
| Rectangular | |
| Actuator Height: | |
| 0.090 inches | |
| Actuator Width: | |
| 0.620 inches | |
| Actuator Color: | |
| White single actuator | |
| Illuminated Actuator Color: | |
| Red single actuator | |
| Actuator Inscription: | |
| Enter/os/data single actuator | |
| Maximum Voltage Rating In Volts: | |
| 115.0 ac and 28.0 dc | |
| Mounting Surface To Terminal End Distance: | |
| 2.620 inches | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Panel | |
| Nonpile-up Contact Arrangement: | |
| 2 pole, double throw, one position momentary single switch unit | |
| Contact Load Current Rating At Maximum Rated Voltage: | |

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

Special Features:

Emi shielded; three way split lens and legend

inductive ac and 2.000 amperes lamp ac

NSN 5930-01-215-7088

Push Switch - Page 2 of 2



Contacts silver

Terminal Type And Quantity:

5 tab, solder lug and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0