

View Online at <https://aerobasegroup.com/nsn/5930-01-215-7089>

Thread Class:

3b all pressure connection

Inside Diameter:

0.437 inches all connections

Hazardous Locations/environmental Protection:

Humidity resistant and salt spray resistant and vibration resistant

Overall Length:

4.000 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Body Length:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.203 inches

Longest Horizontal Distance Between Mounting Centers:

3.000 inches

Longest Vertical Distance Between Mounting Centers:

1.500 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -28.0 degrees celsius and 65.0 degrees celsius

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Decrease

Proof Pressure:

15.00 pounds per square inch gage

Thread Size:

0.437 inches all pressure connection

Mounting Facility Pattern:

Four position rectangular

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 milliamperes resistive load first voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

0.20 actuation point pounds per square inch gage and 0.50 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

5.0 dc at sea level first voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Unf all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0