NSN 5930-01-216-2255

Lock Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-216-2255

Body Style: Bushing mounted Overall Length: 58.19 millimeters Overall Height: 22.5 millimeters Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit Terminal Type And Quantity:
Overall Length: 58.19 millimeters Overall Height: 22.5 millimeters Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
58.19 millimeters Overall Height: 22.5 millimeters Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Overall Height: 22.5 millimeters Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
22.5 millimeters Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Overall Width: 22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
22.5 millimeters Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Bushing Length: 22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
22.23 millimeters Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Body Length: 24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
24.38 millimeters Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Maximum Voltage Rating In Volts: 150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
150.0 ac Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Inclosure Type: Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Fully enclosed Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
Nonpile-up Contact Arrangement: 1 pole, double throw, both positions maintained single switch unit
1 pole, double throw, both positions maintained single switch unit
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A053a0