

View Online at <https://aerobasegroup.com/nsn/5930-01-216-5272>

Thread Pitch Diameters:

+9.450/+9.531 millimeters single mounting facility

Thread Length:

0.275 inches single mounting facility and 0.315 inches single mounting facility

Width Between Flats:

0.184 inches single actuator and 0.187 inches single actuator

Overall Length:

Between 1.620 inches and 1.740 inches

First Flat Length:

0.184 inches single actuator and 0.192 inches single actuator

Shaft Diameter:

0.236 inches single actuator and 0.239 inches single actuator

Shaft Length:

0.315 inches single actuator and 0.320 inches single actuator

Overall Diameter:

1.306 inches

Individual Section Quantity:

1

Nonturn Device Type:

Flatted bushing at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

4 single section front

Throw Quantity:

2 single section front

Mounting Method:

Threaded bushing w/panel seal single mounting facility

Thread Size:

10.0 millimeters single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, parallel flatted, threaded hole single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

0.250 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Iso m single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0