

View Online at <https://aerobasegroup.com/nsn/5930-01-216-8552>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Dustproof and flame resistant

**Overall Length:**

1.375 inches

**Overall Height:**

0.623 inches

**Overall Width:**

0.623 inches

**Body Diameter:**

0.562 inches

**Body Length:**

0.969 inches

**Case Material:**

Metal

**Actuator Diameter:**

0.375 inches

**Actuator Height:**

0.250 inches

**Actuator Color:**

Black single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

2350-01-048-5920 fighting vehicle in

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, double make, momentary action single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 milliamperes resistive dc and 10.000 milliamperes resistive ac

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Data:**

96906-ms25089 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0

**Mil-std (military Standard):**

Mil-s-8805 spec.