

View Online at <https://aerobasegroup.com/nsn/5930-01-216-8725>

**Thread Length:**

0.312 inches single mounting facility

**Overall Length:**

2.469 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Flat Height:**

0.185 inches single actuator and 0.188 inches single actuator

**Shaft Length:**

0.813 inches single actuator

**Nonturn Device Radius:**

0.438 inches at 9: 00 o'clock

**Nonturn Device Type:**

Tab at 3: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Features Provided:**

Cam actuated

**Thread Size:**

0.750 inches single mounting facility

**Contact Voltage Rating In Volts:**

240.0 highest ac voltage rating at sea level

**Switch Actuator Indexing Position Quantity:**

3 single actuator

**Shaft Type:**

Round, slotted, flatted single actuator

**Terminal Type:**

Quick disconnect, male

**Contact Load Current Rating:**

15.0 amperes resistive load lowest ac voltage rating at sea level

**Special Features:**

Ambient compensated; special bimetal circuit

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Thread Series Designator:**

Unf single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0