NSN 5930-01-217-1561

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-217-1561

| Body Style: |
|--|
| Panel mounted |
| Overall Length: |
| 2.032 inches |
| Overall Height: |
| 0.750 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 1.935 inches |
| Body Width: |
| 0.750 inches |
| Body Height: |
| 0.750 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.620 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| Between 0.095 inches and 0.100 inches |
| Actuator Width: |
| 0.620 inches |
| Actuator Color: |
| Black single actuator |
| Illuminated Actuator Color: |
| Red single actuator and green single actuator |
| Actuator Inscription: |
| Ohm (symbol) tk, arrow (symbol) single actuator |
| Illuminated Actuator Color Sequence: |
| Upper half of actuator red, lower half of actuator green |
| Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Lamp holder and full display lens |
| Nonpile-up Contact Arrangement: |
| |

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-217-1561

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 0.500 amperes inductive dc

Precious Material And Location:

Contacts gold

Terminal Type And Quantity:

6 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0