## NSN 5930-01-217-7074

Rotary Switch - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/5930-01-217-7074

**Thread Class:** 

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

**Overall Length:** 

3.685 inches

First Flat Length:

0.250 inches all actuators

Flat Height:

0.216 inches 1st actuator

**Shaft Diameter:** 

0.250 inches 1st actuator

**Shaft Length:** 

0.562 inches 1st actuator

**Overall Diameter:** 

1.344 inches

**Nonturn Device Radius:** 

0.375 inches at 3: 00 o'clock

**Individual Section Quantity:** 

5

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

Pole Quantity:

3 each section front

**Throw Quantity:** 

4 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

**Shaft Flat/slot Angular Location:** 

270.0 degrees from nonturn device 1st actuator

**Rotor Through Connection Quantity:** 

3 each section

**Switch Actuator Indexing Position Quantity:** 

4 all actuators

## NSN 5930-01-217-7074

Rotary Switch - Page 2 of 2

Fiig: A052b0



Shaft Type:
Round, flatted, threaded hole 1st actuator
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees all actuators
Switch Actuator Stop Device Type:
Fixed stop all actuators
Contact Load Current Rating:
200.0 milliamperes resistive load dc at sea level and 20.0 milliamperes inductive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Test Data Document:
81349-mil-s-3786 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef single mounting facility
Specification Data:
81349-mil-s-3786/5 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
Yes - demil/mli