

View Online at <https://aerobasegroup.com/nsn/5930-01-217-8608>

Thread Length:

0.750 inches single mounting facility

Overall Length:

3.780 inches

First Flat Length:

0.450 inches 1st actuator

Flat Height:

0.216 inches 1st actuator

Shaft Diameter:

0.250 inches 1st actuator

Shaft Length:

0.800 inches 1st actuator

Overall Diameter:

1.036 inches

Individual Section Quantity:

1

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Variable resistor provisions

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 1st actuator

Shaft Type:

Round, flatted 2nd actuator

Switch Actuator Positioning Increment:

45.0 degrees 1st actuator

Contact Load Current Rating:

200.0 milliamperes resistive load dc at sea level and 25.0 milliamperes inductive load dc at sea level

Special Features:

Inner shaft rotates freely

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0