NSN 5930-01-217-9170

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-217-9170

Thread Class:

2b single mounting facility

Overall Length:

3.375 inches

Overall Height:

2.719 inches

Overall Width:

2.750 inches

Individual Section Quantity:

3

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Facility Circle Radius:

1.156 inches single mounting facility

Mounting Method:

Bracket and threaded hole single mounting facility

Features Provided:

Actuator knob and dummy section

Thready Qty Per Inch (tpi):

24 single mounting facility

Thread Size:

0.190 inches single mounting facility

Contact Voltage Rating In Volts:

120.0 dc at sea level

Mounting Facility Pattern:

Four position circular single mounting facility

Switch Actuator Indexing Position Quantity:

4 single actuator

Terminal Type:

Tab w/screw

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level

Style Designator:

Tap, circuit selector

Test Data Document:

81349-mil-dtl-15291 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single mounting facility

Specification Data:

81349-mil-dtl-15291/2 government specification

NSN 5930-01-217-9170

Rotary Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0