## NSN 5930-01-218-4040

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-218-4040

| Body Style:   |
|---|
| Hole mounted  |
| Hazardous Locations/environmental Protection:                                     |
| Dustproof   |
| Overall Length:   |
| 3.125 inches  |
| Overall Height:   |
| 2.281 inches  |
| Overall Width:  |
| 1.562 inches  |
| Housing Height:   |
| 1.812 inches  |
| Housing Length:   |
| 3.125 inches  |
| Housing Width:  |
| 1.562 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 1.469 inches  |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width:  |
| 1.156 inches  |
| Maximum Voltage Rating In Volts:  |
| 120.0 ac  |
| End Application:  |
| 2350-01-136-8744 cargo carrier  |
| Inclosure Type:   |
| Fully enclosed  |
| Thready Qty Per Inch (tpi):   |
| 24  |
| Thread Size:  |
| 0.190 inches  |
| Nonpile-up Contact Arrangement:   |
| 1 two circuit, both positions maintained single switch unit                       |
| Switch Actuating Force:   |
| 80.0 inch-ounces  |
| Actuator Movement:  |
| 2.0 differential degrees and 5.0 pretravel degrees                                |
| Contact Load Current Rating At Maximum Rated Voltage:                             |
| 10.000 amperes resistive ac   |
| Precious Material And Location:   |
| Contacts silver   |
| Thread Series Designator:   |

Unc

## NSN 5930-01-218-4040

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 4 screw                     |

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0