NSN 5930-01-218-4040

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-218-4040

| Body Style: |
|---|
| Hole mounted |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Overall Length: |
| 3.125 inches |
| Overall Height: |
| 2.281 inches |
| Overall Width: |
| 1.562 inches |
| Housing Height: |
| 1.812 inches |
| Housing Length: |
| 3.125 inches |
| Housing Width: |
| 1.562 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Length: |
| 1.469 inches |
| Center To Center Distance Between Housing Mounting Facilities Parallel To Width: |
| 1.156 inches |
| Maximum Voltage Rating In Volts: |
| 120.0 ac |
| End Application: |
| 2350-01-136-8744 cargo carrier |
| Inclosure Type: |
| Fully enclosed |
| Thready Qty Per Inch (tpi): |
| 24 |
| Thread Size: |
| 0.190 inches |
| Nonpile-up Contact Arrangement: |
| 1 two circuit, both positions maintained single switch unit |
| Switch Actuating Force: |
| 80.0 inch-ounces |
| Actuator Movement: |
| 2.0 differential degrees and 5.0 pretravel degrees |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 10.000 amperes resistive ac |
| Precious Material And Location: |
| Contacts silver |
| Thread Series Designator: |

Unc

NSN 5930-01-218-4040

Sensitive Switch - Page 2 of 2



| Terminal Type And Quantity: |
|-----------------------------|
| 4 screw |

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0