NSN 5930-01-218-4532

Code Indicating Wheel Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-218-4532

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

4.260 inches

Overall Height:

2.000 inches

Overall Width:

1.150 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

4.090 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Operating Tempurature Range:

-65.0 to 85.0 degrees celsius

Mounting Method:

Bracket and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 all actuators

Terminal Type:

Turret

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

J, f, c, -, 10, 8, 6, 4, 3, 2 5th section

Contact Arrangement Truth Table:

Decimal, 1 pole - 10 positions each section

Color:

White each indicator marking

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

NSN 5930-01-218-4532

Code Indicating Wheel Switch - Page 2 of 2



Style	Desia	nator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0