

View Online at <https://aerobasegroup.com/nsn/5930-01-218-5481>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

1.260 inches

Overall Height:

1.378 inches

Overall Width:

0.945 inches

Mounting Slot Width:

0.135 inches single mounting facility

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

0.970 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.551 inches single mounting facility

Operating Temperature Range:

-65.0 to 85.0 degrees celsius

Mounting Method:

Bracket and slot single mounting facility

Actuator Type:

Thumbwheel single actuator

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

10 single actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

125.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 single section

Contact Arrangement Truth Table:

Bcd complement only, 1 pole - 10 positions single section

Color:

White single indicator marking

Precious Material And Location:

Contact and terminal surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0