## NSN 5930-01-218-7955

Pressure Switch - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5930-01-218-7955
Thread Class:
3a single pressure connection
Overall Length:
2.600 inches
Outside Diameter:
0.437 inches single connection
Overall Diameter:
0.680 inches
Pressure Switch Type:
Absolute
Mounting Method:
Input port
Contact Action Stimulus:
Increase
Proof Pressure:
270.00 pounds per square inch absolute
Thread Size:
0.437 inches single pressure connection
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Sensing Element Burst Pressure:
450.00 pounds per square inch absolute
Terminal Type:
Connector, receptacle
Contact Load Current Rating:
1.1 amperes inductive load single voltage
Contact Adjustability:
Actuation point not adjustable and deactuation point not adjustable
Contact Stimulus Rating:
44.50 actuation point pounds per square inch absolute and 39.50 deactuation point pounds per square inch absolute
Contact Voltage Rating In Volts:
28.0 dc at sea level single voltage
Pressure Connector Type:
Swivel nut, flared, threaded external single connection
Media For Which Designed:
Gas or liquid
Style Designator:
Cylindrical
Thread Series Designator:
Unf single pressure connection

Shelf Life: N/a

## NSN 5930-01-218-7955

Pressure Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0