# NSN 5930-01-218-8936

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-218-8936

## Thread Class:

2a single mounting facility

#### Thread Length:

0.437 inches single mounting facility

## **Overall Length:**

2.691 inches

#### First Flat Length:

0.250 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.437 inches single actuator

#### **Overall Diameter:**

1.306 inches

#### Individual Section Quantity:

2

## Nonturn Device Type:

Slotted bushing at 3: 00 o'clock

## Operating Tempurature Range:

-65.0/+125.0 degrees celsius

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### Pole Quantity:

2 each section front

#### **Throw Quantity:**

2 each section rear

## **Mounting Method:**

Threaded bushing single mounting facility

#### Thread Size:

0.375 inches single mounting facility

## **Contact Voltage Rating In Volts:**

28.0 dc at sea level

## Switch Actuator Indexing Position Quantity:

2 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

## **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-01-218-8936

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment: 45.0 degrees single actuator Contact Load Current Rating: 75.0 milliamperes resistive load ac at sea level Style Designator: Circular wafer, bushing mount Thread Series Designator: Unef single mounting facility Shelf Life: N/a Unit Of Measure: --Demilitarization:

Fiig:

A052b0