NSN 5930-01-219-0870

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-219-0870

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.750 inches
Overall Height:
1.078 inches
Body Diameter:
0.891 inches
Mounting Slot Width:
0.172 inches
Body Height:
0.891 inches
Distance Between Mounting Facility Centers:
1.562 inches
Tempurature Sensing Element Type:
Internal sensor
Operating Tempurature Rating:
350.0 degrees fahrenheit
Mounting Method:
Bracket and slot and surface
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
Contact Load Current Rating: 25.0 amperes resistive load first voltage
-
25.0 amperes resistive load first voltage
25.0 amperes resistive load first voltage Contact Adjustability:
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating:
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts:
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed:
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas
25.0 amperes resistive load first voltage Contact Adjustability: Actuation point not adjustable and deactuation point not adjustable Contact Stimulus Rating: 150.00 actuation point degrees fahrenheit and 110.00 deactuation point degrees fahrenheit Contact Voltage Rating In Volts: 480.0 ac at sea level second voltage Media For Which Designed: Gas Style Designator:

NSN 5930-01-219-0870

Thermostatic Switch - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A048b0