

View Online at <https://aerobasegroup.com/nsn/5930-01-219-2741>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Corrosion resistant

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.400 inches

Body Height:

0.625 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.114 inches

Switch Actuator Quantity:

1

Actuator Length:

1.020 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

0.242 inches

Actuator Roller Diameter:

0.190 inches

Actuator Roller Width:

0.190 inches

Actuator Adapter Style:

Roller arm

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

End Application:

6525-01-130-4930

Inclosure Type:

Fully enclosed

Mounting Method:

Press fit

Pile-up Contact Form Arrangement:

Ak1 single position

Switch Release Force:

1.0 ounces

Switch Actuating Force:

8.0 ounces

Actuator Movement:

Between 0.125 pretravel inches and 0.085 overtravel inches and 0.050 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.250 amperes resistive dc

Special Features:

Terminals are plated for soldering

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0