NSN 5930-01-219-4254

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-219-4254 **Thread Class:** 2b single mounting facility **Overall Length:** 16.440 inches **Overall Height:** 4.125 inches **Overall Width:** 3.125 inches First Flat Length: 0.880 inches single actuator **Shaft Diameter:** 0.375 inches single actuator **Shaft Length:** 0.940 inches single actuator **Individual Section Quantity:** 16 **Longest Horizontal Distance Between Mounting Centers:** 13.500 inches single mounting facility **Longest Vertical Distance Between Mounting Centers:** 2.125 inches single mounting facility **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 6 each section rear **Throw Quantity:** 18 each section rear **Mounting Method:** Base single mounting facility and threaded hole single mounting facility Thready Qty Per Inch (tpi): 32 single mounting facility **Thread Size:** 0.164 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Mounting Facility Pattern:** Four position rectangular single mounting facility **Switch Actuator Indexing Position Quantity:** 18 single actuator **Shaft Type:** Round, v flatted single actuator

Turret

Terminal Type:

NSN 5930-01-219-4254

Rotary Switch - Page 2 of 2



Contact Switching Action: Breaks before makes each section rear **Switch Actuator Positioning Increment:** 20.0 degrees single actuator **Contact Load Current Rating:** 1.8 amperes resistive load dc at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No Fiig: A052b0