## NSN 5930-01-219-4257

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-219-4257

Body Style:			
Hole mounted			
Body Length:			
1.860 inches			
Body Width:			
0.620 inches			
Body Height:			
2.000 inches			
Unthreaded Mounting Hole Diameter:			
0.164 inches			
Center To Center Distance Between Mounting Facilities Parallel To Height:			
1.812 inches			
Actuator Style:			
Round			
Actuator Diameter:			
0.250 inches			
Actuator Height:			
0.525 inches			
Actuator Free Position Height:			
0.525 inches			
Maximum Voltage Rating In Volts:			
125.0 dc			
Inclosure Type:			
Uninclosed			
Mounting Method:			
Threaded hole			
Thready Qty Per Inch (tpi):			
32			
Thread Size:			
0.164 inches			
Nonpile-up Contact Arrangement:			
2 pole, double throw, one position momentary single switch unit			
Switch Release Force:			
4.0 ounces			
Switch Actuating Force:			
Between 6.0 ounces and 14.0 ounces			
Actuator Movement:			
0.105 pretravel inches and 0.150 overtravel inches and 0.105 differential inches			
Contact Load Current Rating At Maximum Rated Voltage:			
500.000 milliamperes resistive dc and 100.000 milliamperes inductive dc			
Thread Series Designator:			

Unc

## NSN 5930-01-219-4257

Sensitive Switch - Page 2 of 2



<b>Terminal</b>	<b>Type</b>	And	Quantity:
-----------------	-------------	-----	-----------

6 tab w/screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0