NSN 5930-01-219-5461

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-219-5461

Body Style:
Panel mounted
Overall Length:
2.510 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Length:
0.688 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Actuator Length:
0.585 inches
Actuator Style:
Rectangular
Actuator Height:
0.180 inches
Actuator Width:
0.585 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and green single actuator
Actuator Inscription:
Wbsv 9 erv 2 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.330 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Full display lens
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Criticality Code Justification:

Feat

NSN 5930-01-219-5461

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Weapon system essential

Test Data Document:

81349-mil-prf-22885/83 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 turret and 5 tab, solder lug

Specification Data:

81349-mil-prf-22885/83 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0

Mil-std (military Standard):

Mil-prf-22885 spec.