

View Online at <https://aerobasegroup.com/nsn/5930-01-219-6972>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.875 inches

Body Length:

1.094 inches

Body Width:

0.406 inches

Body Height:

0.626 inches

Unthreaded Mounting Hole Diameter:

0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.406 inches

Actuator Style:

Round

Actuator Diameter:

0.468 inches

Actuator Height:

1.125 inches

Actuator Free Position Height:

0.250 inches

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.8 ounces

Switch Actuating Force:

7.1 ounces

Actuator Movement:

0.059 pretravel inches and 0.039 overtravel inches and 0.016 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

300.000 milliamperes resistive dc and 15.000 amperes resistive ac

Special Features:

Brass bracket

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0