

View Online at <https://aerobasegroup.com/nsn/5930-01-219-6972>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.406 inches

**Body Height:**

0.626 inches

**Unthreaded Mounting Hole Diameter:**

0.122 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.468 inches

**Actuator Height:**

1.125 inches

**Actuator Free Position Height:**

0.250 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.8 ounces

**Switch Actuating Force:**

7.1 ounces

**Actuator Movement:**

0.059 pretravel inches and 0.039 overtravel inches and 0.016 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

300.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Brass bracket

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0