## NSN 5930-01-220-0864

**Hazardous Locations/environmental Protection:** 

Moisture resistant and salt spray resistant

Push Switch - Page 1 of 2

**Body Style:** Panel mount

Overall Length: 1.200 inches



View Online at https://aerobasegroup.com/nsn/5930-01-220-0864

Overall Height:
3.220 inches
Overall Width:
0.960 inches
Body Length:
0.656 inches
Body Width:
0.960 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
White single actuator and yellow single actuator
Actuator Inscription:
Crypto 1 crypto 2 single actuator
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
End Application:
5895-00-222-4224 communication system
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
$2\ \text{pole},\ \text{double throw},\ \text{both positions maintained single switch unit}$

**Contact Load Current Rating At Maximum Rated Voltage:** 

5.000 amperes resistive dc and 3.000 amperes inductive dc and 10.000 amperes resistive ac

## NSN 5930-01-220-0864

Push Switch - Page 2 of 2



Special	Features:
---------	-----------

Horizontal split lens

**Terminal Type And Quantity:** 

6 turret and 6 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0