

View Online at <https://aerobasegroup.com/nsn/5930-01-220-9681>

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant

Overall Length:

2.260 inches

Overall Height:

1.665 inches

Overall Width:

1.146 inches

Unthreaded Mounting Hole Diameter:

0.100 inches single mounting facility

Individual Section Quantity:

3

Longest Horizontal Distance Between Mounting Centers:

2.090 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

0.900 inches single mounting facility

Mounting Method:

Bracket and unthreaded hole single mounting facility

Actuator Type:

Thumbwheel all actuators

Contact Voltage Rating In Volts:

240.0 dc at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

4 1st actuator

Terminal Type:

Printed circuit

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level

Readout Indicator Marking:

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 3rd section

Contact Arrangement Truth Table:

Bcd, 1 pole - 10 positions each section

Color:

White each indicator marking

Precious Material And Location:

Printed circuit board surfaces gold

Precious Material:

Gold

Style Designator:

Rectangular inline indicating

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0