

View Online at <https://aerobasegroup.com/nsn/5930-01-220-9681>

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant

**Overall Length:**

2.260 inches

**Overall Height:**

1.665 inches

**Overall Width:**

1.146 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches single mounting facility

**Individual Section Quantity:**

3

**Longest Horizontal Distance Between Mounting Centers:**

2.090 inches single mounting facility

**Longest Vertical Distance Between Mounting Centers:**

0.900 inches single mounting facility

**Mounting Method:**

Bracket and unthreaded hole single mounting facility

**Actuator Type:**

Thumbwheel all actuators

**Contact Voltage Rating In Volts:**

240.0 dc at sea level

**Mounting Facility Pattern:**

Four position rectangular single mounting facility

**Switch Actuator Indexing Position Quantity:**

4 1st actuator

**Terminal Type:**

Printed circuit

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level

**Readout Indicator Marking:**

0, 1, 2, 3, 4, 5, 6, 7, 8, 9 3rd section

**Contact Arrangement Truth Table:**

Bcd, 1 pole - 10 positions each section

**Color:**

White each indicator marking

**Precious Material And Location:**

Printed circuit board surfaces gold

**Precious Material:**

Gold

**Style Designator:**

Rectangular inline indicating

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0